

MATERIAL SAFETY DATA

EDITION: 10 DATE: July 2011

1. PRODUCT

NAME: weber.pral D	weber.pral M
weber.rend TTS	weber.rend PTS
weber.rend PTC	weber.rend TUC
weber.rend PUC	weber.rend LAC
weber.rend TTC	weber.rend WCR
weber.rend fibrelite	weber.rend POC
weber.rend MFU	weber.rend RB (RBB & RBF)
weber.rend stipple	weber.rend dash
weber.therm L1	weber.therm L2
weber.therm M1	

Chemical Nature

Odourless powders, containing Portland cement, granular materials and small quantities of other additives.

Manufacturer

Weber

Saint-Gobain Weber Limited
Dickens House
Enterprise Way
Flitwick
Bedford.
MK45 5BY.

EMERGENCY TELEPHONE NUMBER. 08703 330070

2. COMPOSITION

A blend of Portland cement, lime, graded aggregates, fillers and small quantities of other additives.

Portland cement (CAS No.65997-15-1)
EEC Symbol: Xi R Phrases: 36/38

3. HAZARDS IDENTIFICATION

Contains chromium (VI). May produce allergic reaction.

When mixed with water or contact of powder with body fluids produces a strongly alkaline solution. This may cause serious burns and ulceration both to the skin and eyes.

All Portland cement based products, until set, may cause dermatitis due to either their high alkalinity or hexavalent chromium salts present in Portland cement.

4. FIRST AID MEASURES

SKIN CONTACT:	Wash the affected area thoroughly with soap and water. If irritation continues seek medical advice. Clothing contaminated with wet product should be removed and washed thoroughly before reuse.
EYE CONTACT:	Wash eyes immediately with plenty of clean water for at least 15 minutes and seek medical advice without delay.
INHALATION:	Move affected person to fresh air. If nose or airways become inflamed seek medical attention.
INGESTION:	If swallowing has occurred do not induce vomiting. Give person plenty of water to drink. Seek medical attention.

5. FIRE-FIGHTING MEASURES

Portland cement based products are not flammable and will not facilitate combustion of other materials.

Exposure hazards

Do not release water contaminated with Portland cement into surface water drains.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Avoid contact with skin, eyes and clothing. Avoid breathing dust.

Environmental Precautions

Prevent contamination of surface water.

Methods for Cleaning

Recover spillage in dry state if possible. Minimise generation of airborne dust. The product can be slurried with water. Keep children away from clean up operations. Dispose to a place authorised to accept builder's waste. Small quantities can be disposed of as normal household waste.

7. HANDLING AND STORAGE

Handling

When handling bags of Portland cement-based products, due regard should be paid to Manual Handling Operations Regulations.

Some bags may have a small amount of cement dust on their outer surface. Appropriate personal protection should be used whilst handling.

Storage

Bags should be stacked in a safe and stable manner. Store in dry conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Technical Protective Measures

No special measures required

Exposure Limits

Workplace Exposure Limits (OES) Limits 8 hour TWA (According to EH40/05)

Total inhalable dust:	10mg/m ³
Respirable dust:	4mg/m ³

Respiratory Protection

Suitable respiratory protection should be worn to ensure that personal WEL is not exceeded. If care is taken not to raise dust during handling the use of respirators is not normally necessary.

Hand Protection

Wear suitable gloves.

Eye Protection

Suitable goggles or face protection should be worn wherever there is a risk of product powder or product/water mixture entering the eye.

Skin Protection

Wear overalls and closed footwear

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Particulate
Particle size:	5 - 2000 microns
pH:	pH of wet cement 12 - 14

10. STABILITY AND REACTIVITY

Stable under normal room temperature storage conditions. Bags will set solid if continually soaked with water.

11. TOXICOLOGICAL INFORMATION

Eye Contact

Cement constituent is severe eye irritant. Mild exposures can cause soreness. Gross exposures or untreated mild exposures can lead to chemical burning and ulceration of the eye.

Skin Contact

The powder or product/water mixture may cause irritation, contact dermatitis or allergic dermatitis and/or burns.

Inhalation

Inhalation of the powder may cause inflammation of mucous membranes.

Ingestion

The swallowing of small amounts of product or product /water mixtures is unlikely to cause any significant reaction. Larger doses may result in irritation to the gastro intestinal tract.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity Rating

LC50 aquatic toxicity rating not determined. The addition of Portland cement based products to water may, however, cause the pH to rise and therefore may be toxic to aquatic life in some circumstances.

No other specific information available.

Prevent contamination of soil, drains or surface water.

13. DISPOSAL CONSIDERATIONS

Dispose of empty bags or surplus product to place authorised to accept builder's waste according to local regulations. Keep out of reach of children.

14. TRANSPORT INFORMATION

Classification for Transport not required.

15. REGULATORY INFORMATION

Symbol: Xi Irritant
Contains: Portland cement (CAS No.65997-15-1). Contains chromium (VI). May produce an allergic reaction.

R Phrases:
R36/38: Harmful to eyes and skin

S Phrases:
S28: After contact with skin, wash immediately with plenty of soap and water.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39: Wear suitable gloves and eye/face protection.

Keep out of reach of children.

16. OTHER INFORMATION

None.

This safety sheet has been prepared in accordance with the provisions of the EC SDS Directive 91/155.